

Hydraulic Power Packs

Working Pressure 700 bar

Features

- Hydraulic elements, tube fittings, tank accessories and electricals of reputed make
- Robust design with aesthetics and easy to maintain
- Compatible to all reputed brand jacks / cylinders
- Options available: Hand lever / Solenoid (Push button)
- Wheels for easy handling
- Voltages: 110V - 220V - 415V A/C, 50Hz

Single Phase



OPU Series - **O** Orione **P** Power pack **U** Unit **2M** 2HP Single Phase
20 Liters **H** Hand lever operated **S** Single pump
P Push button operated **D** Double pump

Motor HP Single phase	Oil Tank Capacity (ltrs.)	Model	Flow Up to 150 bar (l / min.)	Flow above 150 bar (l / min.)	Usable Oil Capacity (ltrs.)
2	20	OPU-2M-20-HS	-	1.0	12
3	40	OPU-3M-40-HS	-	1.5	25
2	40	OPU-2M-40-HD	4.8	1.0	25
3	40	OPU-3M-40-HD	7.3	1.5	25
2	40	OPU-2M-40-PD	4.8	1.0	25
3	40	OPU-3M-40-PD	7.3	1.5	25

Three Phase



OPU Series - **O** Orione **P** Power pack **U** Unit **2** 2HP Three Phase
20 Liters **H** Hand lever operated **S** Single pump
P Push button operated **D** Double pump

Motor HP Three phase	Oil Tank Capacity (ltrs.)	Model	Flow Up to 150 bar (l / min.)	Flow above 150 bar (l / min.)	Usable Oil Capacity (ltrs.)
2	20	OPU-2-20-HS	-	1.0	12
3	40	OPU-3-40-HS	-	1.5	25
5	50	OPU-5-50-HS	-	2.5	35
7.5	80	OPU-7.5-80-HS	-	3.7	55
2	40	OPU-2-40-HD	4.8	1.0	25
3	40	OPU-3-40-HD	7.3	1.5	25
5	50	OPU-5-50-HD	12.3	2.5	35
7.5	80	OPU-7.5-80-HD	17.3	3.7	55
2	40	OPU-2-40-PD	4.8	1.0	25
3	40	OPU-3-40-PD	7.3	1.5	25
5	50	OPU-5-50-PD	12.3	2.5	35
7.5	80	OPU-7.5-80-PD	17.3	3.7	55

Higher capacity and customized solutions on request. Specifications are subject to change due to continual improvement.

CUSTOMISED SOLUTIONS

